

PRODUCT DESCRIPTION

Constructed of double thick aluminum which has a hammered interior finish polished so to not only be beautiful, but multiply the lumen output. High polish enamel paints finish the exterior for the ultimate reflective surface. The larger sizes are fitted with commercial grade LED and multi-volt input drivers that dim with both ELV and 0-10V functions.

MEASUREMENTS

DIMENSION MAX OAH CANOPY HANGING WEIGHT

 LAMPING

 INPUT VOLTAGE
 : 110-277V

 LUMENS
 : 1,900 Rated (960 Del.)

 BULB
 : 1 x 20W LED PCB Integrated , 20W Total

 BULB INCLUDED
 : (Integrated)

 DIMMABLE
 : Triac, ELV, 0-10V

 CRI
 : 90 CRI

 COLOR_TEMP
 : 3000K

: 24" L x 24" W x 13" H

: 6"W x 1"H x 6"L

: 134" OAH

: 7.05 lb

FINISHES OPTION

Gloss Black / Aluminum

Gloss Navy / Aluminum

Gloss Taupe / Aluminum

Gloss White / Aluminum

MATERIAL

Aluminum

RATINGS

cETLus Dry Location



ADDITIONAL

SLOPE: 30 RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Type:_