

ALUMILUX™ PATH LED | PATHWAY

E41404 | E42404


- ETL, cETL
 - E42400 Rough in Box required for installation of this product.
- Must be installed with 12V Transformer

Job Name : _____

Job Type : _____

Quantity : _____

Comments : _____



PRODUCT DESCRIPTION

Provide safe and functional lighting along your paths by adding spot lighting and bollards. These machined aluminum products enhance the architectural elements of your home by using techniques like grazing and uplighting. Whether you choose to accentuate an object of interest or extend your living space, this collection has the sleek and slim profile to blend seamlessly into your pathways.

MEASUREMENT

MODEL	DIMENSION	HCO	HANGING WEIGHT
E41404	3.25"W x 3.25"H x 1.5"EXT	3.00"	0.55 LB
E42404	3.25"W x 3.25"H x 1.5"EXT	-	0.44 LB

LAMPING

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41404	(1) 2W PCB LED (Integrated)	90+	180	3000K	NO	12V
E42404	(1) 2W PCB LED (Integrated)	80+	180	3000K	NO	120V

FINISHES OPTIONS:

Satin Aluminium (SA)
Bronze (BZ)
White (WT)



MATERIAL:
Aluminium

RATINGS:

ETL cETL IP65
Wet Location
ADA



ADDITIONAL:

INSTALLATION: Down
LIGHTING DIRECTION: Down
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online
PCB LED Integrated

Always consult a qualified electrician before installing any lighting product



Contemporary
Lighting™