

ALUMILUX™ I WALL SCONCE

E41530 | E41532 | E41534

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Dimmable with ELV Dimmer
- Available as: 1-Light, 2-Light, and 3-Light


Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.

SCHEMATIC DIAGRAM



MEASUREMENT

DIMENSIONS : 4.75"W x 4.75"H x 3.5"EXT
HANGING WEIGHT : 2.2 Lb
HCO : 2.5"
BP Width : 4.7"W x 4.7"H

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41530	(1) 3W PCB LED (Integrated)	90+	210	3000K	ELV	120V
E41532	(2) 3W PCB LED (Integrated)	90+	420	3000K	ELV	120V
E41534	(4) 4W PCB LED (Integrated)	90+	840	3000K	ELV	120V

FINISHES OPTIONS:

Bronze (BZ)



MATERIAL:

Aluminum

AVAILABLE MODELS:

E41530 | E41532 | E41534

RATINGS:

ETL cETL IP65
Wet Location
ADA
Title 24 (For Outdoor use)



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40° C (104° F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



Contemporary
Lighting™