

Product Specifications for E22772-91PC	Product S	pecifications	for	E22772	2-91P	С
--	-----------	---------------	-----	--------	-------	---

Job Name:	Job Type:		
0 0	6 .		
Quantity:	Comments		



E22772-91PC

Fizz IV 4-Light LED Flush Mount

FinishGlass/ShadeProduct CategoryPolished ChromeBubbleMini Pendant

Lamping	
Number of Bulb(s)	4
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	7.5
Max Fixture Wattage	30
Rated Life	±4,000 Hours
Rated Lumens	±1,932
Color Temp	±3,300 K
Bulb(s) Included	Integrated
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
	O4 I I /I 4 Â @

Dimmable

Measurements	
Width	13.00"
Height	13.00"
Length	4.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	11.00 lb(s)
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	12.76 lb(s)
"	Carton Width	15.35'
"	Carton Height	7.09'
٩	Carton Length	15.35'
4	Carton Cubic Feet	N/A
٩	Master Pack	1
٩	Master Pack Weight	N/A
4	Master Pack Width	N/A
4	Master Pack Height	N/A
(Master Pack Length	N/A
4	Master Cubic Feet	N/A
4	UPS Shippable	Yes
4		

N/A N/A

Certification	Other	Equivalents

Standard/Lutron® or

Leviton® CL

				-4
Safety Rating	Dry	UPC Code	845094060789	Incandescent Watts
Energy Star	No	Material	N/A	Fluorescent Watts
CA Title 24	No			
CA Title 20	No			
ADA	No			

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.