

Product	Specifica	tions for	F22892	-89PC

Job Name:	Job Type:
Quantity:	Comments



ADA

E22892-89PC **Volt 2-Light LED Vanity**

Finish Glass/Shade **Product Category** Polished Chrome Etched/Bubble **Bath Vanity**

Lamping		Measurements		Shipping
Number of Bulb(s)	4	Width	14.00"	Carton We
Light Type	LED	Height	5.00"	Carton Wi
Bulb Type	LED	Length	N/A	Carton He
Max Bulb Wattage	3	Extension	4.50"	Carton Le
Max Fixture Wattage	12	Back Plate Width	N/A	Carton Cu

Light Type	LED	Height	5.00"
Bulb Type	LED	Length	N/A
Max Bulb Wattage	3	Extension	4.50"
Max Fixture Wattage	12	Back Plate Width	N/A
Rated Life	N/A	Back Plate Height	N/A
Rated Lumens	±840	HCO	1.80"
Color Temp	N/A	Min Overall Height	N/A
Bulb(s) Included	Yes	Max Overall Height	N/A
Light Up/Down	N/A	Hanging Weight	3.74 lb(s)
Beam Spread	N/A	Height Adjustable	N/A
CRI	N/A	Slope	N/A
Photo Cell Included	N/A	Chain Length	N/A
Ballast/Driver/Transformer	No	Wire Length	N/A
Dimmable	N/A	Canopy Width	N/A
		Canopy Height	N/A
		Canopy Length	N/A

Cilipping	
Carton Weight	5.28 lb(s)
Carton Width	7.50"
Carton Height	6.50"
Carton Length	16.50"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes
-	

Certification Other **Equivalents**

No

Safety Rating	Damp	UPC Code	845094070733	Incandescent Watts	N/A
Energy Star	No	Material	N/A	Fluorescent Watts	N/A
CA Title 24	No				
CA Title 20	No				

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.