

Product Specifications for E22221-24PC				
	Job Name:	Job Type:		
	Quantity:	Comments		



ADA

E22221-24PC

Taper 1-Light Mini Pendant

N/A

Finish	Glass/Shade	Product Category
Polished Chrome	Clear	Mini Pendant

Lamping		Measurements		Shipping
Number of Bulb(s)	1	Width	5.00"	Carton Weight
Light Type	LED	Height	21.00"	Carton Width
Bulb Type	LED	Length	N/A	Carton Height
Max Bulb Wattage	2.4	Extension	N/A	Carton Length
Max Fixture Wattage	2.4	Back Plate Width	N/A	Carton Cubic Feet
Rated Life	±40,000 Hours	Back Plate Height	N/A	Master Pack
Rated Lumens	±156	HCO	N/A	Master Pack Weight
Color Temp	±3,500 K	Min Overall Height	N/A	Master Pack Width
Bulb(s) Included	Integrated	Max Overall Height	120.00"	Master Pack Height
Light Up/Down	N/A	Hanging Weight	3.52 lb(s)	Master Pack Length
Beam Spread	N/A	Height Adjustable	Yes	Master Cubic Feet
CRI	N/A	Slope	120°	UPS Shippable
Photo Cell Included	N/A	Chain Length	N/A	
Ballast/Driver/Transformer	No	Wire Length	N/A	
Dimmable	No	Canopy Width	N/A	
		Canopy Height	N/A	

Carton Length	29.13"
Carton Cubic Feet	N/A
Master Pack	6
Master Pack Weight	33.22 lb(s)
Master Pack Width	23.62"
Master Pack Height	16.14"
Master Pack Length	29.92"
Master Cubic Feet	N/A
UPS Shippable	Yes

4.84 lb(s) 7.48" 7.48"

Certification Other **Equivalents**

No

Canopy Length

Safety Rating	Dry UPC Code	845094053101 Incandescent Watts	N/A
Energy Star	No Material	Metal Fluorescent Watts	N/A
CA Title 24	No		
CA Title 20	No		

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.