

## Product Specifications for E95499-101SN

Job Name:	јов Туре:
Quantity:	Comments



## E95499-101SN Elements 4-Light RapidJack Pendant and Canopy

Glass/Shade

## **Product Category**

N/A N/A N/A N/A 1 N/A N/A N/A N/A N/A Yes

		Measurements		Shipping	
	4	Width	34.50"	Carton Weight	
	Xenon	Height	8.50"	Carton Width	
1:	2V GY6.35 T4	Length	6.50"	Carton Height	
	50	Extension	N/A	Carton Length	
	200	Back Plate Width	N/A	Carton Cubic Feet	
	±2,000 Hours	Back Plate Height	N/A	Master Pack	
	±3,000	НСО	N/A	Master Pack Weight	
	±2,900 K	Min Overall Height	N/A	Master Pack Width	
	Yes	Max Overall Height	129.25"	Master Pack Height	
	N/A	Hanging Weight	10.76 lb(s)	Master Pack Length	
	N/A	Height Adjustable	Yes	Master Cubic Feet	
	N/A	Slope	120°	UPS Shippable	
	N/A	Chain Length	N/A		
mer	Yes	Wire Length	63.00"		
	Low-Voltage	Canopy Width	4.5"		
		Canopy Height	2.3"		
		Canopy Length	34.5"		
		Other		Equivalents	

Certification	Other		Equivalents	
Safety Rating	Dry UPC Code	845094044949	Incandescent Watts	N/A
Energy Star	No Material	N/A	Fluorescent Watts	N/A
CA Title 24	No			
CA Title 20	No			
ADA	No			

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.

253 North Vineland Avenue | City of Industry, California 91746 | 800.486.2946p 800.486.7337f | www.et2online.com

## Lamping

Satin Nickel

Finish

Number of Bulb(s)	4
Light Type	Xenon
Bulb Type	12V GY6.35 T4
Max Bulb Wattage	50
Max Fixture Wattage	200
Rated Life	±2,000 Hours
Rated Lumens	±3,000
Color Temp	±2,900 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Low-Voltage