

### Lighting Your Life Since 1970

Product Specifications - 12761WTPN			
Job Name:	Job Type:		
Quantity:	Comments		



### 12761WTPN Rondo 1-Light Wall Sconce

8.5" 6.5" 6.5"

*Finish*Polished Nickel

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±1,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Glass/Shac	le
White	

Measurements	
Width	6.50"
Height	8.50"
Length	N/A
Extension	8"
Back Plate Width	4.50"
Back Plate Height	6.50"
HCO	5.25"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.20 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	
Canopy Height	
Canopy Length	N/A

## **Product Category**

Wall Sconce

hinning

Shipping	
Carton Weight	2.86 lbs
Carton Width	9"
Carton Height	10"
Carton Length	10"
Carton Cubic Feet	0.50
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

# Certification

Certification		Other	
Safety Rating	Damp	UPC Code	783209075375
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	Yes
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Othor

#### **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.