


Lighting Your Life Since 1970

Product Specifications - 20093FTSN Job Name: Job Type: Quantity: Comments



20093FTSN

Aurora 2-Light Invert Bowl Pendant



Finish

Satin Nickel

Glass/Shade

Frosted

Product Category

Invert Bowl Pendant

Lamping

Lamping	
Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	120
Rated Life	±2,500 Hours
Rated Lumens	±1,344
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

1/1/	 	mo	nto

Canopy Length

Weasurements	
Width	16.00"
Height	24.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	14.33 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A

Chinning

Shipping	
Carton Weight	19.18 lbs
Carton Width	19'
Carton Height	17'
Carton Length	20'
Carton Cubic Feet	3.76
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification	Other
Safety Rating	Dry UPC Code
Energy Star	No Shades Included
CA Title 24	No Crystals Included
CA Title 20	No Diffuser Included
ADA	No Conversion Kit
Dark Sky	N/A Material

Equivalents

N/A

N/A N/A Yes N/A Steel

783209054226

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.