

Lighting Your Life Since 1970

Product Specifications - 20907CLPC			
Job Name:	Job Type:		
Quantity:	Comments		



20907CLPC

Sync 6-Light LED Chandelier

Finish Polished Chrome

Lamping

Number of Bulbs	12
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	4.5
Max Fixture Wattage	54
Rated Life	
Rated Lumens	±2,016
Color Temp	±3,000 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Standard/Lutron® CL or Leviton® LED Recommended

GI	lass	s/SI	ha	d	e

Canopy Length

Clear

Product Category	
Single-Tier Chandelie	٤

|--|

Width	27.25"
Height	18.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	36.50"
Hanging Weight	30.80 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	N/A
•	
Canopy Width	N/A
0	N1/A
Canopy Height	N/A

Shipping

Ompping	
Carton Weight	37.40 lbs
Carton Width	13'
Carton Height	10
Carton Length	44'
Carton Cubic Feet	2.99
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

ertification		Other
fety Rating	Dry	UPC C

Safety Rating	Dry	UPC Code	783209110717
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.