

Lighting Your Life Since 1970

# Product Specifications - 25047SWPN/BUI Job Name: Job Type:

Quantity:	Comments



# Finish

Polished Nickel

## Lamping

Number of Bulbs	
Light Type	Incandescer
Bulb Type	M
Max Bulb Wattage	6
Max Fixture Wattage	6
Rated Life	
Rated Lumens	±
Color Temp	
Bulb(s)	Include
Light Up/Down	N//
Beam Spread	N//
CRI	N//
Photo Cell Included	N//
Ballast/Driver/Transformer	Ν
Dimmable	N/

#### Glass/Shade Satin White

	Measurements	
1	Width	10.00"
ent	Height	5.75"
1B	Length	N/A
60	Extension	N/A
60	Back Plate Width	N/A
	Back Plate Height	N/A
±0	НСО	N/A
	Min Overall Height	N/A
ed	Max Overall Height	50.00"
/A	Hanging Weight	4.40 lbs
/Α	Height Adjustable	Yes
/A	Slope	120°
/A	Chain Length	N/A
٩N	Wire Length	36"
I/A	Canopy Width	N/A
	Canopy Height	N/A
	Canopy Length	N/A

25047SWPN/BUI

Mini Hi-Bay 1-Light Pendant W/Bulb

### Product Category Single Pendant

	Shipping	
0"	Carton Weight	4.40 lbs
5"	Carton Width	13"
/A	Carton Height	12"
/A	Carton Length	13"
/A	Carton Cubic Feet	1.09
/A	Master Pack	1
/A	Master Pack Weight	N/A
/A	Master Pack Width	N/A
0"	Master Pack Height	N/A
bs	Master Pack Length	N/A
es	Master Cubic Feet	N/A
0°	UPS Shippable	Yes
/A		
6"		
/A		

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209019492	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Metal		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.