


Lighting Your Life Since 1970

Product Specifications - 25125FTSN				
Job Name:	Job Type:			
Quantity:	Comments			



25125FTSN

Hi-Bay 1-Light Pendant/Wall Sconce/Semi-Flush



Finish

Satin Nickel

Glass/Shade Frosted

Product Category

Single Pendant

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB PAR20
Max Bulb Wattage	50
Max Fixture Wattage	50
Rated Life	±2,000 Hours
Rated Lumens	±550
Color Temp	±2,900 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements

incasul cilicilis	
Width	14.50"
Height	10.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	45.50"
Hanging Weight	4.60 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	72"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Snipping	
Carton Weight	5.81 lbs
Carton Width	7"
Carton Height	17"
Carton Length	10"
Carton Cubic Feet	0.66
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Dry	UPC Code	783209093836
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Metal

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.