


## Lighting Your Life Since 1970

Product Specifications - 2652WSKB		
Job Name:	Job Type:	
Quantity:	Comments	



## 2652WSKB

Pacific 3-Light Semi-Flush Mount



Kentucky Bronze

### Lamping

**Number of Bulbs** 3 **Light Type** Incandescent Bulb Type MB Max Bulb Wattage 75 Max Fixture Wattage 225 Rated Life ±2,500 Hours **Rated Lumens** ±2,400 Color Temp ±2,700 K Bulb(s) Not Included Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No **Dimmable** Standard

## Glass/Shade

Measurements

Wilshire

# **Product Category**

Semi-Flush Mount

Width	18.50"
Height	15.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.50 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shinning

Snipping	
Carton Weight	9.92 lbs
Carton Width	18"
Carton Height	13"
Carton Length	18"
Carton Cubic Feet	2.33
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

#### Certification Other **UPC Code** 783209265288 Safety Rating Dry **Energy Star Shades Included** No N/A CA Title 24 **Crystals Included** N/A No CA Title 20 No Diffuser Included N/A **ADA Conversion Kit** N/A No Dark Sky N/A Material Iron

## Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.