


Lighting Your Life Since 1970

Product Specifications - 2653WSKB				
Job Name:	Job Type:			
Quantity:	Comments			



2653WSKB

Pacific 3-Light Pendant



Finish Kentucky Bronze

Lamping

Lamping	
Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade

Measurements

Wilshire

Width	13.00"
Height	20.50"
Length	44.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	89.00"
Hanging Weight	14.99 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	9.00"
Canopy Height	4.50"
Canopy Length	N/A

Product Category

Island Pendant

Shipping

Carton Weight	20.80 lbs
Carton Width	16"
Carton Height	13"
Carton Length	37"
Carton Cubic Feet	4.45
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Other **Safety Rating UPC Code** 783209265387 Dry **Energy Star Shades Included** No CA Title 24 **Crystals Included** No CA Title 20 No Diffuser Included **ADA Conversion Kit** No Dark Sky N/A Material

Equivalents

N/A

N/A

N/A

N/A

Iron

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.