


Lighting Your Life Since 1970

Product Specifications - 3108WGET				
Job Name:	Job Type:			
Quantity:	Comments			



3108WGET

Whittier Cast 3-Light Outdoor Wall Lantern



Finish Earth Tone

Lamping

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Glass/Shade

Water Glass

Measurements	
Width	10.00"
Height	25.50"
Length	N/A
Extension	14"
Back Plate Width	5.50"
Back Plate Height	17.00"
HCO	12.00"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	12.10 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Outdoor Wall Mount

Shinning

Shipping	
Carton Weight	13.00 lbs
Carton Width	17"
Carton Height	13"
Carton Length	37"
Carton Cubic Feet	4.71
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		Other	
Safety Rating	Wet	UPC Code	783209310803
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Die Cast Aluminum

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.