

Lighting Your Life Since 1970

Product Specifications - 3800LACO		
Job Name:	Job Type:	
Quantity:	Comments	



3800LACO **Balboa DC 1-Light Medium Outdoor Post**

Finish Copper Oxide

Lamping

=amping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Glass/Shade

Lace

Measuremen	its

Width	10.00"
Height	17.25"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.60 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Outdoor Pole/Post Mount

Shinning

Snipping	
Carton Weight	7.70 lbs
Carton Width	13"
Carton Height	13"
Carton Length	26"
Carton Cubic Feet	2.47
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Wet	UPC
Energy Star	No	Shac
CA Title 24	No	Crys
CA Title 20	No	Diffu
ADA	No	Conv
Dark Sky	N/A	Mate

Other	
UPC Code	783209112742
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	DIE CAST ALUMINUM
	, LOMINO M

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.