




Lighting Your Life Since 1970

## Product Specifications - 39720SRPC

Job Name:	Job Type:
Quantity:	Comments:



**39720SRPC**  
**Mimi LED 12-Light Semi-Flush Mount**



### Finish

Polished Chrome

### Glass/Shade

Sunrise

### Product Category

Semi-Flush Mount

### Lamping

Number of Bulbs	12
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	1
Max Fixture Wattage	12
Rated Life	±40,000 Hours
Rated Lumens	±996
Color Temp	±3,500 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	>80
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Lutron® CL or Leviton® LED Dimmer

### Measurements

Width	34.00"
Height	18.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	23.10 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	10"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

### Shipping

Carton Weight	30.50 lbs
Carton Width	30"
Carton Height	12"
Carton Length	30"
Carton Cubic Feet	6.25
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

### Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

### Other

UPC Code	783209098237
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	N/A

### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.