


Lighting Your Life Since 1970

Product Specifications - 39723FMPC		
Job Name:	Job Type:	
Quantity:	Comments	



39723FMPC

Mimi LED 6-Light Pendant



Finish

Polished Chrome

Glass/Shade	
Fume	

Product Category Single Pendant

Lamping
Number of Bulb
Light Type
_ " ''

Number of Bulbs	6
Light Type	LEC
Bulb Type	LEC
Max Bulb Wattage	1
Max Fixture Wattage	6
Rated Life	±40,000 Hours
Rated Lumens	±498
Color Temp	±3,500 k
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	>80
Photo Cell Included	N/A
Ballast/Driver/Transforme	r Yes
Dimmable	Lutron® CL o Leviton® LED Dimme

Measurements	
Width	25.00"
Height	43.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	78.00"
Hanging Weight	23.10 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	10"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Jilippilig	
Carton Weight	27.50 lbs
Carton Width	30"
Carton Height	12"
Carton Length	30"
Carton Cubic Feet	5.99
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cortification

Certification		Other	
Safety Rating	Dry	UPC Code	783209098251
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.