

Lighting Your Life Since 1970

	Product Specifications - 40034CDSE		
I	Job Name:	Job Type:	
I			
İ	Quantity:	Comments	
ı			



40034CDSE

Santa Barbara VX 3-Light Outdoor Wall Lantern

Finish Sienna

Lamping

Number of Bulbs

Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

G	lass/	SI	na	de

Seedy

Measurements

moded on one	
Width	9.00"
Height	16.00"
Length	N/A
Extension	11"
Back Plate Width	6.00"
Back Plate Height	14.00"
НСО	3.50"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	9.02 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Product Category

Outdoor Wall Mount

Shinning

Shipping	
Carton Weight	11.50 lbs
Carton Width	15"
Carton Height	12"
Carton Length	26"
Carton Cubic Feet	2.67
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Dark Sky

Safety Rating Wet **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No

N/A

Canopy Length

Other	
UPC Code	783209063495
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Vive

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.