

Lighting Your Life Since 1970

Product Specifications - 41425WGBK		
Job Name:	Job Type:	
Quantity:	Comments	



41425WGBK

Camden VX 3-Light Outdoor Wall Lantern

Finish Black

Lamping Number of Bulbs

Light Type Incandescent **Bulb Type** CA Max Bulb Wattage 60 Max Fixture Wattage 180 Rated Life ±1,500 Hours **Rated Lumens** ±2.016 Color Temp ±2,700 K Bulb(s) Not Included

Light Up/Down N/A Beam Spread N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No **Dimmable** Standard Dimmer

Glass/Shade Water Glass

Measurements

3

Width 11.00" Height 24.00" Length N/A Extension 14" **Back Plate Width** 5.50" **Back Plate Height** 12.00" HCO 13.50" Min Overall Height 0.00" Max Overall Height N/A **Hanging Weight** 9.81 lbs **Height Adjustable** N/A Slope N/A **Chain Length** N/A Wire Length N/A **Product Category** Outdoor Wall Mount

Chinning

Snipping	
Carton Weight	14.33 lbs
Carton Width	16
Carton Height	14
Carton Length	32
Carton Cubic Feet	3.92
Master Pack	•
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Wet Safety Rating **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No Dark Sky N/A

Canopy Width

Canopy Height

Canopy Length

Other	
UPC Code	783209063990
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Vivex

Equivalents

N/A

N/A

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.