

Lighting Your Life Since 1970

Product Specifications - 4622CLOI				
Job Name: Job Type:				
Quantity:	Comments			



4622CLOI

1-Light Outdoor Wall Mount

Finish Oil Rubbed Bronze

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

G	lass	/SI	ha	d	e

Measurements	

Width	7.50"
Height	13.50"
Length	N/A
Extension	7"
Back Plate Width	N/A
Back Plate Height	N/A
HCO	15.00"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.70 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Product Category

Outdoor Wall Mount

Jilippilig	
Carton Weight	3.20 lbs
Carton Width	7"
Carton Height	13"
Carton Length	8"
Carton Cubic Feet	0.44
Master Pack	6
Master Pack Weight	19.18 lbs
Master Pack Width	13.98"
Master Pack Height	22.83"
Master Pack Length	16.93"
Master Cubic Feet	3.13
UPS Shippable	Yes

Certification

Safety Rating Wet **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No Dark Sky N/A

$\overline{}$	4	L	_	
U	и	1	е	r

Canopy Length

Other	
UPC Code	783209024960
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Solid Brass

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.