

# Lighting Your Life Since 1970

Product Specifications - 48733CLET			
Job Name:	Job Type:		
Quantity:	Comments		



## 48733CLET **Triumph VX 1-Light Outdoor Wall** Lantern

Finish Earth Tone

Lamping

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade

Clear

M	eas	ure	me	nts

Width	10.00"
Height	12.50"
Length	N/A
Extension	7"
Back Plate Width	6.00"
Back Plate Height	8.00"
НСО	6.00"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	11.44 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Product Category** 

Outdoor Wall Mount

### Shippina

Unipping	
Carton Weight	13.00 lbs
Carton Width	14"
Carton Height	10"
Carton Length	16"
Carton Cubic Feet	1.27
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

#### **Safety Rating** Wet **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No Dark Sky N/A

Other	
UPC Code	783209063730
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Vivex

#### **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.