


Lighting Your Life Since 1970

Product Specifications - 55860CLFTAR		
Job Name:	Job Type:	
Quantity:	Comments	



55860CLFTAR

Lighthouse LED 1-Light Medium Outdoor Post



Finish

Anthracite

Glass/Shade

Clear/Frosted

Product Category

Outdoor Pole/Post Mount

Lamping

=amping	
Number of Bulbs	1
Light Type	LEC
Bulb Type	LED
Max Bulb Wattage	7
Max Fixture Wattage	
Rated Life	
Rated Lumens	±455
Color Temp	
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements

Measurements	
Width	8.00"
Height	16.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.70 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Unipping	
Carton Weight	8.40 lbs
Carton Width	12'
Carton Height	12'
Carton Length	23'
Carton Cubic Feet	1.88
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification	Other	
Safety Rating	Wet UPC Code	
Energy Star	No Shades Included	
CA Title 24	Yes Crystals Included	t
CA Title 20	No Diffuser Included	ı
ADA	No Conversion Kit	
Dark Sky	N/A Material	

Equivalents

783209120228

N/A

N/A N/A N/A N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.