

## Lighting Your Life Since 1970

Product Specifications - 85502LACO		
Job Name:	Job Type:	
Quantity:	Comments	



## 85502LACO Balboa DC EE 1-Light Mini Outdoor Wall

**Finish** Copper Oxide

Lamping

Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	13
Rated Life	
Rated Lumens	±900
Color Temp	
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

G	lass	/Sh	ad	e

Measurements

Lace

Product Category	
Outdoor Wall Mount	

N/A

N/A

Width	6.50"
Height	9.50"
Length	N/A
Extension	9"
Back Plate Width	4.50"
Back Plate Height	6.75"
НСО	2.50"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.93 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A

Shipping	
Carton Weight	3.65 lbs
Carton Width	11"
Carton Height	9"
Carton Length	17"
Carton Cubic Feet	0.95
Master Pack	4
Master Pack Weight	15.00 lbs
Master Pack Width	17.25"
Master Pack Height	19.75"
Master Pack Length	22.50"
Master Cubic Feet	4.44
UPS Shippable	Yes

Certification		Other		Equivalents
Safety Rating	Wet	UPC Code	783209112964	Incandescent

**Canopy Height** 

**Canopy Length** 

Safety Rating	wei	UPC Code	783209112964
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	DIE CAST ALUMINUM

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.