

Lighting Your Life Since 1970

	Product Specifications - 85750FSBZ		
ĺ	Job Name:	Job Type:	
ĺ	Quantity:	Comments	



85750FSBZ

Terrace EE 1-Light Medium Outdoor Post

Finish Glass/Shade **Product Category** Outdoor Pole/Post Mount Bronze Frosted Seedy

Lamping	
Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	26
Max Fixture Wattage	26
Rated Life	
Rated Lumens	±1,760
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements

ivieasui eillellis	
Width	8.00"
Height	19.25"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.60 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Snipping	
Carton Weight	8.80 lbs
Carton Width	11"
Carton Height	11"
Carton Length	23"
Carton Cubic Feet	1.68
Master Pack	4
Master Pack Weight	36.40 lbs
Master Pack Width	22.83"
Master Pack Height	24.02"
Master Pack Length	24.02"
Master Cubic Feet	7.62
UPS Shippable	Yes

Certification

Certification	Other
Safety Rating We	t UPC Code 783209113121
Energy Star No.	Shades Included N/A
CA Title 24	Crystals Included N/A
CA Title 20 No	Diffuser Included N/A
ADA No	Conversion Kit N/A
Dark Sky N/A	Material DIE CAST ALUMINUM

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.