


Lighting Your Life Since 1970

Product Specifications - 86104AL			
Job Name:	Job Type:		
Quantity:	Comments		



86104AL **Lightray 1-Light LED Flush Mount**



Finish Brushed Aluminum

Lamping

Number of Bulbs	1
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	15
Max Fixture Wattage	15
Rated Life	
Rated Lumens	±1,050
Color Temp	±3,000 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Standard/Lutron® CL or Leviton® LED Recommended

Glass/Shade

Canopy Height

Canopy Length

Measurements	
Width	5.00"
Height	6.25"
Length	N/A
Extension	5"
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	3.09 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A

Product Category Outdoor Ceiling Mount

Shipping

Cilipping	
Carton Weight	3.86 lbs
Carton Width	7"
Carton Height	8"
Carton Length	7"
Carton Cubic Feet	0.27
Master Pack	4
Master Pack Weight	15.44 lbs
Master Pack Width	15.94"
Master Pack Height	9.21"
Master Pack Length	15.94"
Master Cubic Feet	1.35
UPS Shippable	Yes

Certification		Otner	
Safety Rating	Wet	UPC Code	783209109698
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

N/A

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.