

Lighting Your Life Since 1970

Glass/Shade

Canopy Height

Canopy Length

Recommended

Product Specifications - 87620WTWT				
Job Name:	Job Type:			
Quantity:	Comments			

Product Category

N/A

N/A



Finish

87620WTWT Convert LED Flush Mount

White		White		Flush Mount	
vviite		vviiito		Tradit Would	
Lamping		Measurements		Shipping	
Number of Bulbs		Width	8.00"	Carton Weight	2.88 lbs
Light Type	LED	Height	1.10"	Carton Width	9"
Bulb Type	LED	Length	N/A	Carton Height	4"
Max Bulb Wattage	20	Extension	N/A	Carton Length	9"
Max Fixture Wattage		Back Plate Width	N/A	Carton Cubic Feet	0.20
Rated Life		Back Plate Height	N/A	Master Pack	8
Rated Lumens	±1,400	HCO	N/A	Master Pack Weight	23.06 lbs
Color Temp	2800/2900	Min Overall Height	0.00"	Master Pack Width	18.50"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	9.50"
Light Up/Down	N/A	Hanging Weight	1.80 lbs	Master Pack Length	18.50"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	1.88
CRI	80	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard/Lutron® CL or Leviton® LED	Canopy Width	N/A		

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209111486	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		
-					

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.