

## Lighting Your Life Since 1970

	Product Specifications - 9002SWSN					
ſ	Job Name:	Job Type:				
ſ	Quantity:	Comments				

Product Category



**Finish** 

## 9002SWSN

Glass/Shade

**Essence 2-Light Bath Vanity** 

FIIIISII		Glass/Silaue		Froduct Category	
Satin Nickel		Satin White		Bath Vanity	
Lamping		Measurements		Shipping	
Number of Bulbs	2	Width	14.50"	Carton Weight	4.40 lbs
Light Type	Xenon	Height	6.00"	Carton Width	7"
Bulb Type	G9 Frost	Length	N/A	Carton Height	7"
Max Bulb Wattage	60	Extension	4"	Carton Length	17"
Max Fixture Wattage	120	Back Plate Width	4.63"	Carton Cubic Feet	0.43
Rated Life	±2,000 Hours	Back Plate Height	4.63"	Master Pack	1
Rated Lumens	±1,600	НСО	2.75"	Master Pack Weight	N/A
Color Temp	±2,900 K	Min Overall Height	0.00"	Master Pack Width	N/A
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	3.53 lbs	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard	Canopy Width			
		Canopy Height			
		Canopy Length	N/A		

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209900219	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	Yes	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.