

## Lighting Your Life Since 1970

Product Specifications - 90200FTSN		
Job Name:	Job Type:	
Quantity:	Comments	



## 90200FTSN

Corona 1-Light Mini Pendant

**Finish** Glass/Shade **Product Category** Satin Nickel Frosted

Lamping	
Number of	Bu
<b>Light Type</b>	

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements	
Width	5.00"
Height	6.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	50.50"
Hanging Weight	1.65 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## Mini Pendant

Master Cubic Feet

**UPS Shippable** 

Shipping

Carton Weight	2.20 lbs
Carton Width	7"
Carton Height	7"
Carton Length	13"
Carton Cubic Feet	0.32
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A

N/A

Other **Equivalents** 

Safety RatingDryUPC Code783209108875Incandescent WattsEnergy StarNoShades IncludedN/AFluorescent WattsCA Title 24NoCrystals IncludedN/A
CA Title 24 No Crystals Included N/A
CA Title 20 No Diffuser Included N/A
ADA No Conversion Kit N/A
Dark Sky N/A Material N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.