

Lighting Your Life Since 1970

Product Specifications - 92060FLRB		
Job Name:	Job Type:	
Quantity:	Comments	



92060FLRB

Oak Harbor 1-Light Mini Pendant

FinishRustic Burnished

Lamping

Number of Bulbs 1 **Light Type** Incandescent Bulb Type MB Max Bulb Wattage 100 Max Fixture Wattage 100 Rated Life ±2,500 Hours **Rated Lumens** ±1,150 Color Temp ±2,700 K Bulb(s) Not Included Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

Glass/Shade

Frost Lichen

Othor

Measurements

Width 6.00" Height 14.38" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height 0.00" 59.25" Max Overall Height **Hanging Weight** 3.52 lbs Height Adjustable N/A Slope 120° **Chain Length** N/A Wire Length 72" **Canopy Width** N/A **Canopy Height** N/A **Canopy Length** N/A

Product Category Mini Pendant

Shipping

Snipping	
Carton Weight	5.00 lbs
Carton Width	7"
Carton Height	9"
Carton Length	13"
Carton Cubic Feet	0.46
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification	Other
Safety Rating	Dry UPC Code
Energy Star	No Shades Included
CA Title 24	No Crystals Included
CA Title 20	No Diffuser Included
ADA	No Conversion Kit
Dark Sky	N/A Material

Equivalents

783209050112

N/A N/A N/A N/A Iron

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.