

Lighting Your Life Since 1970

Product Specifications - 92750WTPN			
Job Name:	Job Type:		
Quantity:	Comments		



92750WTPN

Rondo 1-Light Mini Pendant

Finish

Polished Nickel

Lamping

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±1,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

(G	ì	a	s	S	/S	h	a	d	е	

Measurements

Canopy Length

Othor

White

Mini Pendant

Width	8.50"
Height	9.75"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	54.50"
Hanging Weight	2.38 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	72"
Canopy Width	N/A
Canopy Height	N/A

Product Category

Shipping

Carton Weight	4.70 lbs
Carton Width	12"
Carton Height	9"
Carton Length	15"
Carton Cubic Feet	0.89
Master Pack	1
Mantar Dook Waight	NI/A

15" 0.89 N/A Master Pack Weight Master Pack Width N/A **Master Pack Height** N/A Master Pack Length N/A **Master Cubic Feet** N/A **UPS Shippable**

Cortification

Certification		Other	
Safety Rating	Dry	UPC Code	783209075412
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	Yes
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.