

MAXIM Assembly Instruction For 22305PN

1. Through the nut(C) to the steel shade(O), cross spider(D) and metal washer(R); then secured by ball(S) till tight
2. Secured the tube (J) to the nipple (K) till tight
3. Put the metal ring (I), part (G1), decorated part (H) and part (G) to the tube(J); then secured by metal ring (F) till tight
4. Secured the tube (E) to the tube (J)
5. Secured the tube (B2) to the tube (E)
6. Secured the tube (B1) to the tube (B2)
7. Secured the tube (B) to the tube (B1)
8. Secured the ceiling pan (A) to the tube (B)
9. Secured the nipple(Q) to the coupler (L); then secured by hex nut (P) till tight
10. Put the rubber washer (M1), glass diffuser (X), rubber washer (M) and metal washer(N) to the decorated flat metal; (Z), the secured by nut (V) till tight
11. Put the metal washer (W) and rubber washer (U) to the nipple (Q)
12. Put the glass diffuser (X) and decorated flat metal(Z) into the steel shade(O), and put the metal washer (W1) and rubber washer (U1) to the nipple (Q), then secured by the hex nut(P1) till tight
13. Put the cap (T) to the glass diffuser (X); then secured by part (Y) till tight
14. Install 6*60W type A bulbs into socket of the fixture(bulbs not included)

