

VISOR | Wall Sconce

24752 / 24754 / 24756 / 24758

- cETLus
- Suitable for Damp locations
- Frosted Acrylic diffuser
- 3000K Color Temperature
- ADA Compliant
- CRI 90+

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

Dual Black aluminum channels support a Frost acrylic diffuser that projects light into the room when illuminated. Available in 4 lengths, this collection can be installed horizontal above the mirror or vertical on each side.

MEASUREMENTS

MODEL	DIMENSION	BACKPLATE	HCO	WIRE LENGTH
24752	18"W x 4.75"H x 0.50"EXT	4.75"H x 4.75"W x 1.5"Depth	2.25"H	10"L
24754	24"W x 4.75"H x 0.50"EXT	4.75"H x 6"W x 1.5"Depth	2.25"H	10"L
24756	30"W x 4.75"H x 0.50"EXT	4.75"H x 6"W x 1.5"Depth	2.25"H	10"L
24758	36"W x 4.75"H x 0.50"EXT	4.75"H x 7.75"W x 1.5"Depth	2.25"H	10"L

LAMPING

MODEL	BULB TYPE	TOTAL BULB	CRI	LUMENS INIT	DEL	COL TEMP.	DIMMABLE	INPUT
24752	19W PCB LED (Integrated)	2	90+	1520	850	3000K	Triac CL	120V
24754	25W PCB LED (Integrated)	2	90+	2000	1125	3000K	Triac CL	120V
24756	30W PCB LED (Integrated)	2	90+	2400	1350	3000K	Triac CL	120V
24758	36W PCB LED (Integrated)	2	90+	2880	1620	3000K	Triac CL	120V

FINISHES OPTIONS:

Black (BK)



GLASS:

Frosted (FT)

MATERIAL:

Aluminum + Acrylic + Steel

AVAILABLE SIZE:

18" | 24" | 30" | 36"

RATINGS:

cETLus
 Damp Location
 ADA
 Dimmable



ADDITIONAL:

INSTALLATION: Horizontal/ Vertical
 LIGHTING DIRECTION: Indirect
 RATED LIFE: 50,000 hours

Always consult a qualified electrician before installing any lighting product