

# RAIL LED I Bath Vanity

## 52100 / 52102 / 52103 / 52104


- ETL, cETL IP65
- Suitable for damp locations
- CRI 90+
- Dimmable with Triac Dimmer
- Energy Star
- Title 24 JA8 Compliant

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_



### PRODUCT DESCRIPTION

Tubular shaped White acrylic diffusers mount to frames of Polished Chrome, Satin Nickel, or Black. Powered by 3000K LED these fixtures work well in a variety of contract applications.



### MEASUREMENTS

#### MODEL DIMENSION

52100	18"L x 4.75"H x 2.50"EXT
52102	24"L x 4.75"H x 2.50"EXT
52103	30"L x 4.75"H x 2.50"EXT
52104	36"L x 4.75"H x 2.50"EXT

#### HANGING WEIGHT

0.70 LB
0.85 LB
1.10 LB
1.30 LB

### LAMPING

MODEL	BULB TYPE	LUMENS		COL TEMP.	DIMMABLE	INPUT
		CRI	RATED DEL			
52100	(1) 12W LED (Integrated)	90+	1140 930	3000K	Triac Dimmer	120V
52102	(1) 16W LED (Integrated)	90+	1520 1400	3000K	Triac Dimmer	120V
52103	(1) 20W LED (Integrated)	90+	1900 1690	3000K	Triac Dimmer	120V
52104	(1) 24W LED (Integrated)	90+	2280 2040	3000K	Triac Dimmer	120V

### FINISHES OPTIONS:

- Satin Nickel (SN)
- Polished Chrome (PC)
- Black (BK)



### MATERIAL:

Aluminum + Acrylic

### RATINGS:

- ETL cETL IP65
- Damp Location
- Energy Star
- Title 24 JA8 Compliant
- ADA
- Dimmable



### ADDITIONAL:

RATED LIFE : 50,000 hours  
 INSTALL UP/DOWN: Both  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)

*Always consult a qualified electrician before installing any lighting product*