ILLUMINAIRE II | FLUSH MOUNT

57680 | 57682 | 57683 | 57684

- Die Cast Aluminum
- Size options between 5", 7", 9", and 11"
- Available in 3000k (Made-to-order Color Temperatures available)
- Thick acrylic etched on the inside to give dimension
 Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Polished Chrome (PC), Satin Nickel (SN), and Bronze (BZ)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box (pancake and mud ring acceptable)
- Pendant light accessory available (sold separately)
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65









Job Name : _____

Quantity : ___


Job Type : _____



57600 **PENDANT ACCESORY** (Sold Separately, Fixture NOT included)

PRODUCT DESCRIPTION

Our ever popular flush mount available in an updated form. Featuring die-cast aluminum bases available in Satin Nickel, Polished Chrome or Bronze with dimensional acrylic diffusers, Clear on the outside and Frost on the inside creating an intriguing optical effect. With increased lumens and better pricing this collection is the second generation in an already famous collection. Use the optional pendant adapter to convert any size to a hanging fixture.



MEASUREMENTS

MODEL	DIMENSION	LENGHT
57680	5"W x 1.75"H x 5"L	8"L
57682	7"W x 1.75"H x 7"L	8"L
57683	9"W x 1.75"H x 9"L	8"L
57684	11"W x 1.75"H x 11"L	8"L

LAMPING

			COL LUMENTS		.113			
	MODEL	BULB TYPE	CRI	TEMP.	RATED	DEL	DIMMABLE	INPUT
	57680	12.5W AC Integrated LED	90+	3000K	920	820	Triac CL	120V
	57682	15W AC Integrated LED	90+	3000K	1080	980	Triac CL	120V
	57683	18W AC Integrated LED	90+	3000K	1270	1170	Triac CL	120V
	57684	20W AC Integrated LED	90+	3000K	1400	1300	Triac CL	120V

COL

HIMFNS

WIDE

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

Polished Chrome (PC) Satin Nickel (SN) Bronze (BZ)



GLASS:

Clear + Frosted Acrylic (CLFT)

MATERIAL:

Acrylic + Aluminum

AVAILABLE SIZE:

5" | 7" | 9" | 11"

RATINGS:

ETL/cETL Wet Location Dimmable Title 24 JA8 Compliant **Energy Star**









ADDITIONAL:

RATED LIFE: 35,000 hours WARRANTY: 5 Years

