
WAFER LED I SURFACE MOUNT

57720 / 57722 / 57724


- Die Cast Aluminum
- Size options between 4.5", 6.25" and 9"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), Black (BK), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65





PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

 MODEL
 DIMENSION

 57720
 4.5"L x 4.5"W x 0.5"H

 57722
 6.25"L x 6.25"W x 0.5"H

 57724
 9"L x 9"W x 0.5"H

LAMPING

MODEL	BULB TYPE
57720	10W PCB LED (Integrated)
57722	15W PCB LED (Integrated)
57724	20W PCB LED (Integrated)

HANGING WEIGHT							
0.99 lb							
1.21 lb							
1.80 lb							

CRI			DIMMABLE	INPUT
90+	700 600	3000K	ELV	120V
90+	1050 900	3000K	ELV	120V
90+	1400 1200	3000K	ELV	120V
	90+ 90+	CRI INIT DEL 90+ 700 600 90+ 1050 900	LUMENS COL CRI INIT TEL 90+ 700 600 3000K 90+ 1050 900 3000K 90+ 1400 1200 3000K	CRI INIT DEL TEMP. DIMMABLE 90+ 700 600 3000K ELV 90+ 1050 900 3000K ELV

Always consult a qualified electrician before installing any lighting product



FINISHES OPTIONS:

White (WT) Bronze (BZ) Black (BK) Satin Nickel (SN)



MATERIAL: Die Cast Aluminum

PMMA Acrylic Diffuser

AVAILABLE SIZES:

4.5" | 6.25" | 9"

RATINGS:

ETL/CETL IP65 Wet Location Energy Star Title 24 JA8 compliant ADA Closets Rated: NEC 410.8 & 410.16



ADDITIONAL: RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online