

# WAFER LED | SURFACE MOUNT

## 57720 / 57722 / 57724


- Die Cast Aluminum
- Size options between 4.5", 6.25" and 9"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_



### PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



### MEASUREMENTS

#### MODEL DIMENSION

57720	4.5"L x 4.5"W x 0.5"H
57722	6.25"L x 6.25"W x 0.5"H
57724	9"L x 9"W x 0.5"H

#### HANGING WEIGHT

0.99 lb
1.21 lb
1.80 lb

### LAMPING

#### MODEL BULB TYPE

57720	10W PCB LED (Integrated)
57722	15W PCB LED (Integrated)
57724	20W PCB LED (Integrated)

CRI	LUMENS	COL	TEMP.	DIMMABLE	INPUT
INIT	DEL				
90+	700	600	3000K	ELV	120V
90+	1050	900	3000K	ELV	120V
90+	1400	1200	3000K	ELV	120V

### FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



### MATERIAL:

Die Cast Aluminum  
 PMMA Acrylic Diffuser

### AVAILABLE SIZES:

4.5" | 6.25" | 9"

### RATINGS:

ETL/cETL IP65  
 Wet Location  
 Energy Star  
 Title 24 JA8 compliant  
 ADA  
 Closets Rated: NEC 410.8 & 410.16



### ADDITIONAL:

RATED LIFE: 50,000 Hours  
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)  
 PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product

