WAFER LED LINEAR I SURFACE MOUNT


57746 / 57747

- Edge-Lit Technology
- Aluminum extruded body for better heat dissipation
- Available in 3000K / 4000K color temperature
- Dimmable with ELV dimmer at 120V
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- 120-277 Input Voltage
- Energy Star listed
- Easy to install: Fits 4" Outlet Box
- Not recommended for pancake box
- Suitable for Wet location
- ETL/cETL, IP65

Job Name : ______ Job Type : ______ Quantity : ______ Comments :

PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS	
DIMENSIONS	: 48"L x 4.5"W x 0.5"H

HANGING WEIGHT : 3.97 lb HCO : 0.5" BP Width : 4.1" LAMPING INPUT VOLTAGE : 120-277 LUMENS : 3200 Rd

BULB

CRI

DIMMABLE

: 120-277V : 3200 Rated (2500 Del.)

MAX OH : 0.5"

MIN OH : 0.5"

: 36W PCB LED (Integrated) : ELV Dimmer at 120V : 90+

 Model
 Color Temp.

 57746
 3000K

 57747
 4000K

PMMA Acrylic Diffuser

MATERIAL:

Aluminum

FINISHES OPTIONS:

White (WT)

RATINGS: Closets Rated: NEC 410.8 & 410.16 ETL/CETL IP65 Wet Location Energy Star



ADDITIONAL: RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product

