

WAFER LED | SURFACE MOUNT

58720 / 58722 / 58724 / 58738 / 58739


- Patent Pending Construction
- 120 - 277 input
- Die Cast Aluminum
- Size options: 5", 7", 9", and 15"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

MODEL DIMENSION

58720	5"L x 5"W x 0.5"H
58722	7"L x 7"W x 0.5"H
58724	9"L x 9"W x 0.5"H
58738	15"L x 15"W x 0.5"H
58739	15"L x 15"W x 0.5"H

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
			INIT DEL			
58720	10W PCB LED (Integrated)	90+	800 650	3000K	ELV	120V -277
58722	15W PCB LED (Integrated)	90+	1250 1000	3000K	ELV	120V -277
58724	20W PCB LED (Integrated)	90+	2250 1800	3000K	ELV	120V -277
58738	30W PCB LED (Integrated)	90+	3000 2400	3000K	ELV	120V -277
58739	30W PCB LED (Integrated)	90+	3000 2400	4000K	ELV	120V -277

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



MATERIAL:

Die Cast Aluminum
 PMMA Acrylic Diffuser

AVAILABLE SIZES:

5" | 7" | 9" | 15"

RATINGS:

ETL/cETL IP65
 Wet Location
 Energy Star
 Title 24 JA8 compliant
 ADA
 Closets Rated: NEC 410.8 & 410.16



ADDITIONAL:

RATED LIFE: 50,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product